

TV2 & DV2

COMMERCIAL THROUGH RETAIL NON-VENDED TOP LOAD WASHER & MATCHING DRYER

Built for Reliable Performance

Speed Queen® two-speed top load washers and matching dryers are durably constructed using premium materials for long-lasting, reliable performance and superior results. If you want your laundry done right, you want a Speed Queen. Our machines are manufactured using metal instead of plastic. They're built with rugged, commercial-grade construction. Our world-class test lab rigorously pushes our products far beyond the conditions they're likely to ever face. We work hard at every point of our manufacturing process to ensure that our machines reflect that belief.



TV2 Control Panel



DV2 Control Panel

Washer:


- Durable stainless steel wash tub
- Extract speed of 710 RPM spins clothes out drier
- Automatic Balancing Suspension provides the industry's best out-of-balance handling, completing wash cycles without interruption
- Curved four-vane polypropylene agitator provides 210° agitation stroke which delivers superior washability

Dryer:

- Door is reversible for installation flexibility
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Efficient and fast dry cycle



COMMERCIAL THROUGH RETAIL NON-VENDED TOP LOAD WASHER & MATCHING DRYER



TV2



DV2

Product Code	TV2000WN	
Control Option	Mechanical Knob	
Color	White	
Capacity - lb (kg)	16 (7.2)	
Cylinder Volume - cu.ft. (liters)	3.19 (90.3)	
Spin Speed G-Force (RPM)	150 (710)	
Motor Size - HP (kw)	0.5 (0.37)	
Water Consumption Per Cycle - g (liter)*	27.9 (106)	
IWF (Water Factor) - gal/ft ³ (liters/liter/cycle)*	8.8 (1.18)	
MEF ₃₂ (Modified Energy Factor) ft ³ /kWh/cycle (Liters/kWh/cycle)*	1.35 (38.2)	
Available Water Temperatures	Hot, Warm, Cold	
Available Cycles	Soak/Prewash, Heavy Duty/Permanent Press, Normal Eco, Delicate	
Electrical Requirements (v/Hz/Ph-Amp)	120/60/1 - 15 Amp	
Water Pressure - p.s.i (bar)	20-120 (1.4/8.3)	
Drain	Pump	
Cylinder Finish	Stainless Steel	
Net Weight - lb (kg)	186 (84.4)	
Shipping Weight - lb (kg)	196 (88.9)	
Shipping Dimensions Approx. - in	Width	28.25
	Depth	30
	Height	45
Agency Approvals	cULus	
Model No.	LWN432SP115TW01	

Product Code	Gas: DV2000WG Electric: DV2000WE	
Control Option	Mechanical Knob	
Color	White	
Capacity - lb (kg)	18 (8.2)	
Cylinder Volume - cu.ft. (liters)	7.0 (198)	
Motor (Thermal Protected)	0.33 HP	
Type of Gas (Gas Models Only)	Factory Equipped Natural/Mixed Gas	
Air Outlet Diameter - in	4	
Exhaust Airflow - cfm (liters/sec)	220 (105)	
Available Cycles	Automatic Permanent Press/Knits, Automatic Regular/Delicate, Time Dry	
Electrical Requirements	**Electric	120/208/240/60/1-30 Amp
	Gas	120/60/1-15 Amp
Heating Element	Electric	5350W, 240V / 4750W, 208V
	Gas	22,500 Btu
Net Weight - lb (kg)	130 (58.9)	
Shipping Weight - lb (kg)	140 (63.5)	
Shipping Dimensions Approx. - in	Width	30.5
	Depth	29.5
	Height	45
Agency Approvals	cULus	
Model No.	LDE30RGS173TW01 LDG30RGS113TW01	

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
TV2000WN	25.625	43	28	53	-
DV2000WE/DV2000GE	26.875	43	28	15.44	23.5

For Commercial Use Only

* Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.
 ** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.
 Gas dryers can be field converted for operation on LP gas with optional 649P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

AR23-0086

Speed Queen by Alliance Laundry Systems